


N-TYPE SOLAR PANEL

PS560W#BPVN

560_W

BIFACIAL MODULE

Industry-leading Warranty based on nominal power



Features



SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



Excellent weak light performance

More power output in weak light condition, such as cloudy, morning and sunset



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Hot 2.0 Technology

The N-type module with Hot 2.0 technology has better reliability and lower LID/LETID.



Extended wind and snow load tests

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal) *




Lower LCOE

Higher bifaciality, higher power output and lower BOS cost



MECHANICAL SPECIFICATIONS

Cell Type	N type Mono-crystalline
Cell Dimensions	182*182mm
Cell Arrangement	144 (6*24)
Weight	32KG
Module Dimensions	2278*1134*30mm
Cable Length	Portrait 300mm/Landscape 1200mm/Customized
Cable Cross Section Size	TUV: 4mm ² /UL: 12AWG
Front Glass	2.0mm, Anti-Reflection Coating
Back Glass	2.0mm, Heat Strengthened Glass
No. of Bypass Diodes	3/6
Packing Configuration	36pcs/pallet, 720pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68



ELECTRICAL SPECIFICATIONS

Module Type	PS560W#BPVN	
Testing Condition	STC	NMOT
Rated output (Pmp/Wp)	560	421
Maximum Power Voltage(Vmpp/V)	41.9	39.3
Maximum Power Current(Imp/A)	13.37	10.69
Open Circuit Voltage(Voc/V)	50.7	48.1
Short Circuit Current(Isc/A)	14.13	11.41
Module efficiency(%)	21.7%	
Power Tolerance (W)	0~+5	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s

MAXIMUM RATINGS

Maximum System Voltage	1000V/1500V DC (IEC)
Operating Temperature	-40°C ~ +85°C
Maximum Series Fuse	30A
Static Loading	Snow Loading: 5400Pa/ Wind Loading: 2400Pa
Conductivity at Ground	≤0.1Ω
Safety Class	II
Resistance	≥100MΩ
Application Level	Class A

TEMPERATURE CHARACTERISTICS

NMOT Temperature	45°C±2°C
Temperature Coefficient (Pmax)	-0.30%/°C
Temperature Coefficient (Voc)	-0.25%/°C
Temperature Coefficient (Isc)	0.046%/°C

CURVE & TEMPERATURE DEPENDENCE

